

# Telephone, Ethernet & Data Fiber Optic Multiplexer

## Model TC8520

- Multiplexes 10/100 Ethernet, 2-Wire Analog POTS or 2/4-Wire 600 Ohm Analog and Optional RS-232, RS-422, TTL, Dry Contact
- Network Management (Web, Telnet)
- One Fiber Bi-Directional Communication Optic Option
- Multimode or Single Mode (1300/1550nm)
- Power Redundancy, Optical Redundancy Optional
- 12VDC, Optional 24VDC, -48VDC, 125VDC or 115/230VAC
- Industrial Hardened (optional)
- Hi-Temp2 Version Exceeds NEMA & Caltrans Traffic Control Specs



TC8520P 19" Wide, 1U High Rackmount Version

The TC8520 Telephone, Ethernet & Data Fiber Multiplexer multiplexes various combinations of 2-wire Analog POTS or 2/4-Wire 600 Ohm Analog, 1 Ch. 10/100 Ethernet or Serial Data channels over single mode (1300/1550nm) or multimode fiber (1300/1550nm).

The TC8520 supports distances to more than 100 km and offers one fiber bi-directional optic option communication option to maximize fiber cable usage. Optional redundant power and optics include automatic switchover for maximum reliability.

Setup, diagnostics and control is accessed via Serial Terminal, Telnet management ports. Diagnostics include LED indicators, dry contact alarms and local and remote loopback.

The Ethernet port supports full 10Mbps bandwidth and rate control in increments of 32Kbps. It is IEEE 802.3/802.3u/802.3x compliant.

The TC8520 converts 2-wire FXS to fiber optics on the telephone side with ring down capability and FXO on the PBX side. Because the TC8520 digitizes the analog signals (PCM), voice quality does not degrade over extended distances. Serial interface options are RS-232, RS-422, TTL, Dry Contact.

The TC8520 is available basic standalone or 1U high "pizza box." Fiber optic connectors are ST, FC or SC. Standard power is 12VDC and includes built-in redundancy. Optional power sources include 24VDC, -48VDC, 125VDC or 115/230VAC with an external power cube. High temperature (-20°C to 70°C) and extreme temperature (-40°C to 80°C) versions are also available.



## Applications

Typical applications include extending SDH/SONET backbones and adding Telephone Voice or 2/4-Wire 600 Ohm Analog, Ethernet and Serial service to existing fiber optic links. Service Providers use the TC8520 as an efficient, cost effective method to provide their customers with Telephone Voice, Ethernet and Serial connections. The one fiber bi-directional communication, option can double usage of existing fiber optic cable plants.

TC Communications, Inc.  
17881 Cartwright Rd. Irvine, CA 92614 U.S.A.  
Tel: (949) 852-1972, Fax: (949) 852-1948  
Sales: (800) 569-4736  
Web Site: [www.tccomm.com](http://www.tccomm.com)  
E-mail: [sales@tccomm.com](mailto:sales@tccomm.com)



Typical Application Using TC8520 Telephone, 10/100 Ethernet & Serial Data Fiber Optic Multiplexers

### Data Rates

Telephone.....300Hz to 3.4 KHz  
 Ethernet .....10/100 Mbps  
 .....(10 Mbps throughput)  
 RS-232 .....Up to 128 Kbps Async  
 .....64 Kbps Sync  
 RS-422, TTL .....Up to 19.2Kbps

### Channel Capacity

2/4-Wire 600 Ohm Analog.....4  
 Telephone.....4  
 Ethernet.....1  
 RS-232, RS-422, TTL .....4

### Optical

Transmitter.....ELED/LASER\*  
 Receiver .....PIN Diode  
 Wavelength  
 .....1300nm Multimode  
 .....1300/1550nm Single Mode  
 Optical Connectors.....ST , FC, SC  
 Loss Budgets\* - .....  
 LED/ELED.....15dB MM @62.5/125µm  
 LASER.....20dB SM @9/125µm

### Electrical

Interface.....2-wire Analog POTS  
 .....2/4-Wire 600 Ohm Analog  
 .....IEEE 802.3 Ethernet  
 .....RS-232, RS-422, TTL  
 Ethernet Connector.....RJ45F  
 2-wire Analog Connector.....RJ11F  
 RS-232, RS-422, TTL.....RJ45

### System

Bit Error Rate .....1 in 10<sup>10</sup> or Better

### Visual Indicators

System LEDs.....PWR A, PWR B, Vcc  
 Channel Status (each port).....RXD,  
 .....RLOS, LOS, RLPB, BPV, Alarm  
 Optical Signal Status .....SyncB  
 .....Optic in Use, RXA, RXB, VLIN

### Diagnostic Functions

Local and Remote Loopback

### Power

Standard .....12VDC @ 1.2A  
 Optional .....24VDC, -48VDC,  
 .....125VDC, 115/230VAC

### Temperature

Operating.....-10°C to 50°C  
 Hi-Temp1 (optional) ....-20°C to 70°C  
 Hi-Temp2 (optional) ....-40°C to 80°C  
 Storage.....-40°C to 90°C  
 Humidity.....95% non-condensing

### Physical (Standalone Unit)

Height.....(6.70 cm) 2.6"  
 Width.....(18.14 cm) 7.1"  
 Depth.....(24.8 cm) 9.8"  
 Weight.....(1.36 kg) 3.0 lbs

\*Contact factory for higher requirements

\*\* Future release



SAI GLOBAL  
 ISO 9001  
 Quality

TC Communications, Inc.  
 17881 Cartwright Road  
 Irvine, CA 92614 U.S.A.  
 Factory Tel: (949) 852-1972  
 Fax: (949) 852-1948

Sales Office  
 International  
 (949) 852-1973

Web Site: [www.tccomm.com](http://www.tccomm.com)  
 E-mail: [sales@tccomm.com](mailto:sales@tccomm.com)