

# Universal Rack Mount Card Cage

# Models TCRM191/192

- 4 U Height (7")
- Dual Power Capability with Automatic Switchover in the Event of Failure
- Universal Switching Power Supply Accepts 90 to 264VAC (47 to 63 Hz)
- Optional -48VDC Power Supply
- Overload & Short-Circuit Protection



TCRM191/192 rack mount card cage (shown with with optional power cards)

The TCRM191 and TCRM192 Universal Rack Mount Card Cages hold up to 10 single multiplexer or modem-type cards, or up to 5 double-multiplexer or double-modem type cards. In general the TCRM191 is used for multiplexers and the TCRM192 for modems.

Both can operate with one power supply or dual load-sharing power supplies. The AC power supply automatically adjusts for 90 to 264VAC input and 47 to 63 Hz operation. The DC power supply accepts -48VDC input. The AC and DC power supplies can be mixed in the same unit.

The dual load-sharing power supplies feature automatic switchover in the event of a power failure. The power switch and its LED are located on the front panel.

Both rack assemblies are 19" wide by 7" high. The TCRM191 is 9" deep and the TCRM192 is 5.25" deep.



## Applications

TC Card Cages are designed with sturdy construction to house TC products in standard 19" Racks.

TC Communications, Inc.  
17881 Cartwright Rd. Irvine, CA 92614 U.S.A.  
Tel: (949) 852-1972, Fax: (949) 852-1948  
Sales: (800) 569-4736  
Web Site: [www.tccomm.com](http://www.tccomm.com)  
E-mail: [sales@tccomm.com](mailto:sales@tccomm.com)